



Mobile 2-post lift

FHB3000-04-SL-2300

article no.: FHB3000-04

Portable lift, capacity 3000 kg, 400 V power supply, electro-hydraulic drive, asymmetric swivel arms, drive-in width 2300 mm, for cars, SUV, small vans



specifications


article no.		FHB3000-04
lifting unit	quantity of columns	2
load support	load support	4 swivel arms, asymmetric
	capacity	3 t
	length of swivel arm at front, minimum (mm)	600 mm
	length of swivel arm at front, maximum (mm)	1070 mm
	length of swivel arm at rear, minimum (mm)	700 mm
	length of swivel arm at rear, maximum (mm)	1550 mm
	distance between supports, maximum	2780 mm
	load pad Ø	120 mm
lifting height	height adjustment of load pad	35 mm
	lifting height / floor version	1850 mm
speed	lifting time	40 sec.
	lowering time (under load)	40 sec.
drive	mode of drive	electro-hydraulic
	motor	AC voltage
	motor power (kW)	2.2 KW
power supply	type of power supply	mains supply
	electrical connection	400V/3Ph+N+PE/50Hz
	fuse (Amps)	16 A
operation	mode of operation	1 central control unit
	control	electric
regularisation	synchronisation	master-slave cylinder system
travelling device	travelling device	2 front wheels, 1 detachable wheel handle at rear
load securing	load securing	hydraulic and mechanical
dimensions	length	2350 mm
	width	3350 mm
	height	790 mm
	drive-in width	2300 mm
weight		1100 kg
protection class		IP54
surface treatment	type of surface treatment	powder coating
	colour	orange RAL2004 / grey RAL7015



accessories



FHB3000-LA02
4 extension tubes, 100 mm



FHB3500-Z-UG
U-guidances for rubber pads



FHB3000-FA3-2300
2 platforms, 2.75 t, length 3.5 m, to drive-on with cars