

BUCCESPEED

WHEEL ALIGNMENT



32HPR 32HP 32SP 32L






SPEED32HPR/HP

The SPEED32 series is the second generation of Butler 3D wheel aligners. Its innovative system of totally wireless 3D cameras with Bluetooth transmission can be used on different types of lifts thanks to its automatic flatness compensation. Its compact size also makes it suitable for those workshops having limited space.





SPEED32L



System with measuring heads directly connected to the lift, in this way eliminating the space occupied by the tower in front of the lift.

Bluetooth communication between the measuring heads and console.

Compact and extremely lightweight measuring heads. 5MP resolution for measurement and compensation of the lifting platform level, also on an irregular surface.

Every measuring head has an LCD display for the basic information and five keys for remote software navigation; remote control function.

LED repeaters that permit recording without having to view the monitor. (Only for model HPR and HP)

MEASURING HEADS



A Built-in handle with plastic protection.

Built-in rubber protection.



Rapid pivoting coupling system to the lift to prevent damage in the case of obstacles in descent.




One only head position to measure different wheel base vehicles.

SPEED32HPR.3 - SPEED32HR3 SPEED32SR3 - SPEED32L3





Set of 4 self-centring 3-point clamps, without compensation, to achieve quick and precise measurement. Equipped with a rapid movement system and ABS claws; no metal-metal contact.



The 3D targets installed on the clamps are extremely lightweight, are maintenance-free and have no electronic components. All angles of the vehicle are measured in only a few seconds without any operator intervention.



Batteria con sistema di sgancio veloce. Durata della batteria di 8 ore per consentire un lavoro in officina prolungato per l'intera giornata.

Battery with quick release system. 8-hour battery lifetime to permit extended full day work.

Batterie mit Schnellstecksystem. Acht Stunden Batterielaufzeit zur Gewährleistung eines ununterbrochenen Betriebs über den gesamten Arbeitstag.

Batterie à système de décrochage rapide. Autonomie de 8 heures des batteries pour assurer des journées entières de travail dans le garage.

Batería con sistema de liberación rápida. Duración de la batería de 8 horas para permitir un trabajo en el taller prolongado durante toda la jornada.

SPEED32SP.4 - SPEED32L.4





Set of 4 self-centring 4-point clamps to achieve quick and precise measurement.



The 3D targets installed on the clamps are extremely lightweight, are maintenance-free and have no electronic components. All angles of the vehicle are measured in only a few seconds without any operator intervention.

SPEED32HPR/HP

SPEED32SP

Compartment for storing keyboard and mouse.

Closed cabinet in lightweight materials making movement easier; with space optimised for storing equipment.






Easy to reach battery charger.

SPEED32L

Dedicated hooks for storing the measuring heads.


Open cabinet very light in movement; with optimised space for storing equipment.




Screen 22".

Easy to reach battery charger.













International data bank with vehicle technical data sheets and possibility to create a customer data bank for adjustment recording. Management software and display in Windows environment, always connected with the Wi-fi USB flash drive. Simple and intuitive thanks to high resolution graphics.

















Model	HPR	HP	SP.3	SP.4	L.3	L.4
STDA160 Kit containing 2 batter	es 🔮	©	©	©	©	©
STDA141ADAS Token for ADAS pane positioning	9	©	©	©	©	©
STDAPREMIUM Token for additional fu ctions	n- ③	②	•	•	•	•
STDA38K Set for 4-point quick locking clamp	•	•	•	©	•	©
STDA35E 3-point clamps with tar	get 🤣	Ø	9	•	Ø	•
STDA33EU 4-point clamps with tai	get •	•	•	Ø	•	Ø
STDA124 1 pair of turn tables	9	②	©	©	©	©
S110A7 1 pair of turn tables	•	•	9	Ø	Ø	②
10479 Brake pedal depresse	r 🥝	0	Ø	Ø	0	Ø
SDA161 Steering wheel lock	Ø	Ø	Ø	Ø	Ø	Ø
STDA158 Wheelalignment-ON (Wi-fi USB flash driv. included)	9	9	9	9	9	9
STDAShoot&Go Token for consulting da base on-line	ta- 📵	©	©	©	©	©

TECHNICAL	SPEED32HPR/HP SPEED32SP
FEATURES	SPEED32L
	,
Partial toe	+/- 20°
Total toe	+/- 20°
	+/- 20°
Cornering toe	
Camber	+/- 10°
Caster	+/- 18°
King pin (SAI)	+/- 18°
Setback	+/- 5°
Setback front axle	+/- 5°
Geometric centre line	+/- 5°
Thrust angle	+/- 5°
Max. steering angle	+/- 50°
Minimum tyre size	8"
Max. tyre size	24"
Max. wheel diameter	910 mm
Max. wheelbase	4500 mm



Engineering and Marketing S.p.A. a.s.u.
Via dell'Ecologia 6 - 42047 Rolo (RE)
Ph. +39-0522-647911 - Fax +39-0522-649760
www.butler.it - info@butler.it

Member of VSG - Vehicle Service Group a DOVER company

