



Portable partnership for small workshops

Belt driven 1 stage compressors Base plate compressors

Reliable quality performance

- Longer compressor lifetime due to less heat: large cooling fins and specially designed flywheel
- Enhanced tools efficiency and reliability with aluminium aftercooler
- Both moveability and stability: large wheels and double front feet or blockable wheels
- Safety first with robust metal belt guard and rubber handle

Suited for mobile workbench






Impact wrench CP7759Q

Partnumber	Type	Comp.	Liters	l/m	cfm	m3/h	HP	kW	rpm	volt/Hz	phase	bar	psi	L x W x H (mm)	kg/Lb
4116024324	CPRC 227 NS12S MS	1	27	255	9,0	15,3	2,0	1,5	1075	230/50	1	10	145	830 x 370 x 710	46/101
4116024325	CPRC 227 NS12S MT	1	27	255	9,0	15,3	2,0	1,5	1075	400/50	3	10	145	830 x 370 x 710	46/101
4116024326	CPRC 250 NS12S MS	1	50	255	9,0	15,3	2,0	1,5	1075	230/50	1	10	145	780 x 370 x 780	55/121
4116024327	CPRC 250 NS12S MT	1	50	255	9,0	15,3	2,0	1,5	1075	400/50	3	10	145	780 x 370 x 780	55/121
4116024328	CPRC 290 NS12S MS	1	90	255	9,0	15,3	2,0	1,5	1075	230/50	1	10	145	1000 x 410 x 820	67/147
4116024329	CPRC 290 NS12S MT	1	90	255	9,0	15,3	2,0	1,5	1075	400/50	3	10	145	1000 x 410 x 820	67/147
4116024330	CPRC 390 NS12S MS	1	90	320	11,3	19,2	3,0	2,2	1350	230/50	1	10	145	1000 x 410 x 900	69/152
4116024331	CPRC 390 NS12S MT	1	90	320	11,3	19,2	3,0	2,2	1350	400/50	3	10	145	1000 x 410 x 900	69/152
4116024332	CPRC 3150 NS12S MS	1	150	320	11,3	19,2	3,0	2,2	1350	230/50	1	10	145	1380 x 420 x 950	85/187
4116024333	CPRC 3150 NS12S MT	1	150	320	11,3	19,2	3,0	2,2	1350	400/50	3	10	145	1380 x 420 x 950	85/187
4116024334	CPRC 3200 NS12S MS	1	200	320	11,3	19,2	3,0	2,2	1350	230/50	1	10	145	1500 x 450 x 960	129/284
4116074062	CPRF 20 NS12 BTT	1	0	320	9,0	15,3	2,0	1,5	1075	400/50	3	10	145	640 x 320 x 360	28/62

CPRC 250 NS12S MS

Partnumber 4116024326


Technology	 Piston 10 bar
Use	 Intermittent
Air quality	 Standard
Noise level	 Standard
Vessel size	 50l



Stability



Moveability



Lower air temperature enhances tools efficiency



CPRC 290 NS12S MS

Partnumber 4116024328

Technology	 Piston 10 bar
Use	 Intermittent
Air quality	 Standard
Noise level	 Standard
Vessel size	 90l



Simultaneous use