

The ultimate reference in car service

Belt driven 2 stage compressors

Top performance at 11 bar

- More air and higher pressure with dual compression
- High reliability thanks to motor performance, low wear cast iron cylinder, and stainless steel valve plates
- Safety first with the clear and userfriendly pressure switch and metal belt guard
- Enhanced tools efficiency and reliability with aluminium aftercooler, and extra intercooler on NS39 pump

Suited for 2 / 3 operators



Impact wrench CP7748




Partnumber	Type	Comp.	Liters	l/m	cfm	m3/h	HP	kW	rpm	volt/Hz	phase	bar	psi	L x W x H (mm)	kg/Lb
4116022856	CPRD 4200 NS29S MT	2	200	514	18,1	30,8	4,0	3,0	1400	400/50	3	11	160	1500 x 450 x 960	140/308
4116022857	CPRD 4200 NS29S FT	2	200	514	18,1	30,8	4,0	3,0	1400	400/50	3	11	160	1500 x 450 x 960	137/302
4116022858	CPRD 4270 NS29S MT	2	270	514	18,1	30,8	4,0	3,0	1400	400/50	3	11	160	1530 x 600 x 1160	147/324
4116022859	CPRD 4270 NS29S FT	2	270	514	18,1	30,8	4,0	3,0	1400	400/50	3	11	160	1530 x 600 x 1160	144/317
4116022860	CPRD 6270 NS39 MT	2	270	653	23,1	39,2	5,5	4,0	1000	400/50	3	11	160	1520 x 590 x 1260	180/397
4116022861	CPRD 6500 NS39 MT	2	500	653	23,1	39,2	5,5	4,0	1000	400/50	3	11	160	2030 x 680 x 1400	250/551
4116022862	CPRD 6500 NS39 FT	2	500	653	23,1	39,2	5,5	4,0	1000	400/50	3	11	160	2030 x 680 x 1400	250/551

CPRD 4200 NS29S MT

Partnumber 4116022856

Technology	 Piston 11 bar
Use	 Intermittent
Air quality	 Standard
Noise level	 Standard
Vessel size	 200l



Dual compression high air delivery



Safe and user-friendly



CPRD 6270 NS39 MT

Partnumber 4116022860

Technology	 Piston 11 bar
Use	 Intermittent
Air quality	 Standard
Noise level	 Standard
Vessel size	 270l



Lower air temperature enhances tools efficiency



Simultaneous use