



For accurate tire servicing

Belt driven 2 stage compressors Baseplate compressors

Performant units for all your car tire applications

- Performant air and higher pressure with large dual compression pumps
- Enhanced tools efficiency and reliability with aluminium aftercooler, and extra intercooler on NS39 and NS59S pump
- Longer compressor lifetime due to less wear and heat: low running motor speed
- Easy maintenance: quick filter cleaning and replacement, and oil sight glass
- Safety first with the clear and userfriendly pressure switch and metal belt guard

Suited for 1 / 2 operators



Impact wrench CP7782-6

Partnumber	Type	Comp.	Liters	l/m	cfm	m3/h	HP	kW	rpm	volt/Hz	phase	bar	psi	L x W x H (mm)	kg/Lb
4116022863	CPRD 8270 NS39 MT	2	270	827	29,2	49,6	7,5	5,5	1250	400/50	3	11	160	1520 x 590 x 1260	210/462
4116022864	CPRD 8270 NS39 FT	2	270	827	29,2	49,6	7,5	5,5	1250	400/50	3	11	160	1520 x 590 x 1260	210/462
4116022865	CPRD 8500 NS39 MT	2	500	827	29,2	49,6	7,5	5,5	1250	400/50	3	11	160	2030 x 680 x 1400	280/617
4116022866	CPRD 8500 NS39 FT	2	500	827	29,2	49,6	7,5	5,5	1250	400/50	3	11	160	2030 x 680 x 1400	280/617
4116022867	CPRD 8270 NS59S MT	2	270	950	33,5	57,0	7,5	5,5	750	400/50	3	11	160	1520 x 590 x 1260	210/462
4116022868	CPRD 8270 NS59S FT	2	270	950	33,5	57,0	7,5	5,5	750	400/50	3	11	160	1520 x 590 x 1260	210/462
4116022871	CPRD 8500 NS59S MT	2	500	950	33,5	57,0	7,5	5,5	750	400/50	3	11	160	2030 x 680 x 1400	290/639
4116022872	CPRD 8500 NS59S FT	2	500	950	33,5	57,0	7,5	5,5	750	400/50	3	11	160	2030 x 680 x 1400	290/650
4116022884	CPRD 6270 B5900 VS	2	270	653	23,1	39,2	5,5	4,0	1400	400/50	3	11	160	850 x 970 x 2100	210/462
4116000161	CPRF 80 NS59S BTT	2	0	950	33,5	57,0	7,5	5,5	750	400/700/50	3	11	160	1090 x 640 x 810	130/287
4116000163	CPRF 80 NS59S BFT	2	0	950	33,5	57,0	7,5	5,5	750	400/700/50	3	11	160	1100 x 640 x 800	130/287