

► D-ES 54-11250

CONDENSATE TREATMENT SYSTEMS

EASY HANDLING & EXCELLENT FILTRATION

- **Simpler, less messy operation**
Innovative cartridges make oil-water separation easier and cleaner
- **Low maintenance**
4,000-hour service interval
- **Supreme waste water purity**
Waste water achieves high purity with oil content as low as 5 ppm at outlet
- **Improved filtration for a cleaner environment**
Also removes oil from stable emulsions



OPTIONS

- Overflow indicator
- Manifold for multiple condensate inlet
- Wall mounting kit
- Spill Container

TECHNICAL SPECIFICATIONS

Model	Max capacity - Mild climate <i>without</i> dryer & filters			Max capacity - Mild climate <i>with</i> dryer & filters			Dimensions					
	l/s	m³/hr	cfm	l/s	m³/hr	cfm	A	B	C	Weight	Connections	
							mm (in)	mm (in)	mm (in)	kg (lb)	Condensate inlet	Water outlet
D-ES 54	15	54	32	12	43	25	250 (10)	147 (6)	216 (9)	1.2 (2.6)	6mm (1/4")	10mm (3/8")
D-ES 113	31	113	66	25	90	53	250 (10)	147 (6)	216 (9)	1.5 (3.4)	6mm (1/4")	10mm (3/8")
D-ES 225	63	225	132	50	180	106	390 (15)	278 (11)	428 (17)	5.8 (12.7)	2 x 1/2"	1/2"
D-ES 383	106	383	225	85	306	180	397 (16)	286 (11)	507 (20)	7.7 (16.9)	2 x 1/2"	1/2"
D-ES 765	213	765	450	170	612	360	490 (19)	396 (16)	576 (23)	13.1 (28.9)	2 x 1/2"	1/2"
D-ES 1350	375	1350	795	300	1080	636	583 (23)	446 (18)	721 (28)	25.3 (55.7)	2 x 3/4"	3/4"
D-ES 2813	781	2813	1655	625	2250	1324	692 (27)	568 (22)	970 (38)	45.1 (99.4)	2 x 3/4"	3/4"
D-ES 5625	1563	5625	3311	1250	4499	2648	975 (38)	782 (31)	1000 (39)	86 (189.5)	2 x 3/4"	3/4"
D-ES 11250	3125	11250	6621	2500	8998	5296	975 (38)	1600 (63)	1000 (39)	171.9 (379.1)	2 x 3/4"	3/4"

Sizes above are available with Activated Carbon or Organoclay. Selection to be done based on each application.

Reference conditions:

Relative air humidity: 60%
Air inlet temperature: 25°C (77°F)
Running hours per day: 12 hrs
Effective working pressure: 7 bar (102 psi)

Correction factors:

Relative humidity	%	0.5	0.6	0.7	0.8	0.9		
	Correction factor	1.10	1.00	0.85	0.74	0.66		
Ambient temperature	°C	15	20	25	30	35	40	
	Correction factor	1.33	1.17	1.00	0.76	0.50	0.30	
Running hours per day	hrs	12	14	16	18	20	22	24
	Correction factor	1	0.86	0.75	0.67	0.6	0.55	0.5

69991000000 © 2026, C. Aria C. S.R.L. All rights reserved.
C. Aria C. S.R.L. reserves the right to change or revise specifications and product design in connection with any features of our products. Such changes do not entitle the buyer to corresponding changes, improvements, additions or replacements for equipment previously sold or shipped. Read all safety instructions in the manual before usage.